

# Camspec

## The M508 Basic Programmable, UV-Vis, Spectrophotometer

### MAIN FEATURES

- Stepper motors for wavelength and filters
- Stores up to 200 methods/results
- Concentration calibration: up to 8 standards and up to 3 replicates, linear or linear through zero
- Selectable wavelength calibration and dark current measurement
- 200 - 1000nm wavelength range
- 4nm bandwidth
- Low stray light (0.1%T at 220nm and 340nm)
- Large sample compartment (up to 100mm pathlength cells)
- 2 x 10mm UV cells and 4 x 10mm glass cells included
- Large selection of accessories
- Manual 4-cell changer
- PC Application Software option for wavelength scanning, concentration curves and timescan
- USB socket for PC Control and USB for data export. Bluetooth printer interface
- Data output includes method number and name, wavelength, date and time, %T, Abs
- Test Tube holder
- And many more accessories



### Technical Specifications for the M508 UV/VIS Spectrophotometer

Display	4 lines x 20 character LED
Light sources	Tungsten-Halogen and Deuterium
Monochromator	1200 lines/mm grating
Detectors	Silicon Photodiode
Wavelength Range	200 - 1000nm
Wavelength Accuracy	± 2 nm
Wavelength Repeatability	± 1 nm
Noise	< 0.001A @ 500nm 0A
Zero Drift	< 0.003A per hour after warm-up
Bandpass	4 nm
Stray Light	<0.1%T @ 220nm and 340nm
Photometric Accuracy	+/- 1% 0-2 A
Photometric Range	-1 to 2.5A, 0-125%T and -9999C and +9999C
Printer Interface	Bluetooth
Computer Interface	USB for PC control plus USB for data export
Power Requirements	110/120V, 220/230V, 50/60 Hz, 135VA
Dimensions	510 x 420 x 210 packed 645 x 535 x 370
Weight	14Kg packed 17Kg

Email: [sales@camspec.eu](mailto:sales@camspec.eu)

Tel: +44 (0) 113 286 4536

[www.camspec.eu](http://www.camspec.eu)

# Camspec

## User Interface

The user interface of the M508 Single Beam Spectrophotometer includes Basic Mode (Abs, %T), Quantitative (concentration calibration curves), Kinetics (including timedrive), DNA/Protein. In Basic Mode, the result is continuously displayed (no need to "press to read")

## PC Control

The M508 has a USB output for the transfer of results to a PC and for PC control of the M508. Comprehensive Camspec Application Software is available, together with small PC programs, dedicated to specialist tasks.

## A selection of the many Cell Compartment Accessories available

Test-tube holder (100mm) P/N 501-101

Adjustable micro-cell holder P/N 501-102 (illustration)

4 x 10mm manual cell changer P/N 501-114

4-cell holder for 5-50mm cells P/N 501-104

4-cell holder for 100mm cells P/N 501-103 (illustration)

100mm cylindrical cell holder P/N 501-106

Thermostatted single cell holder (requires water bath) P/N 508-105


Sipper, processor controlled P/N 508-121

Peltier system for 10mm cells, 15-40°C P/N 508-123

Peltier/Sipper system combined P/N 508-124

Calibration standards for wavelength, absorbance, stray light (traceable to international standards)

M508/M108 PC application system software (including PC cable) P/N 108-110



Email: [sales@camspec.eu](mailto:sales@camspec.eu)

Tel: +44 (0) 113 286 4536

[www.camspec.eu](http://www.camspec.eu)