

HANDHELD MEASURING DEVICE SETS

**GMH 5630-L02**

Art. no. 607470

Waterproof dissolved O₂ handheld measuring device, including sensor GWO 5610, 2 m cable**GMH 5650-L02**

Art. no. 607474

Waterproof dissolved O₂ handheld measuring device, including sensor GWO 5610, 2 m cable, with data logger and alarm**Varianten:****GMH 5630-L04**

Art. no. 606881

GMH 5630 handheld measuring device with sensor with 4 m cable length

GMH 5630-L10

Art. no. 607471

GMH 5630 handheld measuring device with sensor with 10 m cable length

GMH 5630-L30

Art. no. 607472

GMH 5630 handheld measuring device with sensor with 30 m cable length

GMH 5650-L04

Art. no. 606883

GMH 5650 handheld measuring device with sensor with 4 m cable length

GMH 5650-L10

Art. no. 607478

GMH 5650 handheld measuring device with sensor with 10 m cable length

GMH 5650-L30

Art. no. 607479

GMH 5650 handheld measuring device with sensor with 30 m cable length

Accessories and spare parts:**GKK 5001**

Art. no. 611606

with cut-outs for 1 device of the GMH 5xxx-/7500 series and accessories for water analysis (395 x 295 x 106 mm)

GKK 5240

Art. no. 602068

Durable case, suitable for universal applications with individual configuration of the foam insert, pressure equalisation possible, waterproof. Dimensions: 520 x 415 x 200 mm



OXYGEN MEASURING DEVICE



READY-TO-USE

GOX 20

Art. no. 600126

Oxygen measuring device, operative, incl. oxygen probe and battery

Specifications:**Measuring range****Temperature:** 0.0 ... 40.0 °C**Oxygen:** 0.0 ... 20.0 mg/l O₂**Resolution****Temperature:** 0.1 °C**Oxygen:** 0.1 mg/l O₂**Accuracy (at nominal temperature = 25 °C) ±1 digit****Temperature:** ±0.3 °C (in range 0 ... 30 °C)**Oxygen:** ±2 % of m.w. ±0.2 mg/l**Electrode:**

active diaphragm type. Electrode-Ø front: approx. 12 mm, length: approx. 170 mm, connecting cable approx. 2 m permanently connected to device.

Response time: 95 % in 10 s, depending on temperature**Operation life:** approx. 3 years or more depending on maintenance**Operation pressure:** max. 3 bar**Temperature compensation:** automatically via temperature sensor integrated in electrode**Calibration:** simple quick-calibration in atmospheric air**Display:** 3½-digit LCD display, 13 mm high**Working temperature:** 0 ... 50 °C**Power supply:** 9V battery**Battery life:** approx. 300 h**Housing:** impact-resistant ABS housing**Dimensions:** 106 x 67 x 30 mm (H x W x D)**Weight:** approx. 250 g (ready for use)**Scope of supply:** device incl. electrode, battery, GWOK01 and KOH electrolyte, manual**Accessories and spare parts:****GWOK 01**

Art. no. 601411

Spare diaphragm head

KOH 100

Art. no. 603356

Spare electrolyte 100 ml

GSKA 3610

Art. no. 607267

Protective cap made of gunmetal, salt water resistant, submerged, also suitable for use with greater depths or with a flow